AFCONA – 3779

Chemical Composition

Polyacrylic polymer

Product general description

Levelling agent for solvent-based coatings

Product Properties

AFCONA-3779 is a pure polyacrylic levelling agent. Polyacrylic are well known for flow and leveling performance. AFCONA-3779 also acts as defoamer in most coating systems.

AFCONA-3779:

- 1) improves levelling
- 2) works as defoamer and deareator
- 3) provides anti-flooding and floating
- 4) does not interfere with intercoat adhesion

AFCONA-3779 is especially suitable for:

- 1) unsaturated polyester
- 2) coil and can coatings, especially can coating.
- 3) polyurethane coatings
- 4) stoving enamels
- 5) two-pack epoxy compounds
- 6) air-drying alkyd systems

Product specification

Active ingredients 50 - 52%

Solvent	xylene / isobutanol / Tripropylene Glycol monomethyl ether
Density at 20 °C	$0.97 - 0.99 \text{ g/cm}^3$
Colour	max.3
Appearance	transparent to slightly yellowish liquid

Addition and dosage

0.3 - 2.0% on total formulation. In general, under normal conditions, the dosage is 0.3 - 0.8% based on total formulation.

Incorporation

AFCONA-3779 should be added at the end of the batch preparation

Storage

AFCONA-3779 should be stored in a cool dry place. When kept in an original unopened container, it will keep up to 5 years from the date of manufacture. The expiry date is indicated on the container.

Packaging

25 kg and 190 kg non-returnable containers

AFCONA ADDITIVES SDN BHD (711366-U)

10, Jalan Anggerik Mokara, 31/63, Kota Kemuning, 40460, Shah Alam, Selangor, Malaysia. Tel : +603-5122 2289 Fax : +603-5122 8289 Web Site : www.afcona.com / www.afcona.com.my This datasheet is intended to give technical guidance without any obligation