

# AFCONA – 6700



## Chemical Composition

Based on ketoxime and a phosphorous ester salt

## Product general description

Anti-gel agent and viscosity stabilizer for air-drying and stoving coating systems

## Product Properties

AFCONA-6700 is an anti-gel additive for air-drying alkyds and stoving coating systems.

In air-drying alkyd paints, the ketoxime in AFCONA – 6700 form a protection layer on the top of the paint to reduce the oxidation caused by oxygen.

However, AFCONA – 6700 mainly is used in stoving paints to avoid gel during storage. AFCONA – 6700 will block the reactive group of the melamine and will re-release it at 80 - 100°C for further reaction. AFCONA-6700 can significantly prolong the shelf life of a coating.

## Product specification

Solvents	Isobutanol / Xylene / Water
Density at 20 °C	0.87 - 0.89 g/cm <sup>3</sup>
Refractive index	1.427 – 1.437
Flashpoint	24°C
Appearance	transparent to slight yellowish liquid

## Addition and dosage

0.5 - 1.0 % on total formulation

## Incorporation

AFCONA-6700 should be added after grinding. Already gelled materials can be restored to processing viscosity by the addition of AFCONA-6700. In such cases, the addition levels should be two or three times higher than given above.

## Storage

AFCONA-6700 should be stored in a cool dry place. When kept in an original unopened container, it will keep up to 5 years from the date of manufacture. The expiry date is indicated on the container.

## Packaging

25 kg and 180 kg non-returnable containers