

AFCONA - 7204



Chemical Composition

Defoamer with Polysiloxane and foam destroying polymer

Product general description

Defoamer with good compatibility but considerable as excellent defoamer

Product Properties

AFCONA – 7204 is recommended for UPE, polyvinyl, epoxy, polyurethane resin systems where it gives good transparency to systems.

AFCONA – 7204 can be used in all UPE application but most suitable for transparent casting, transparent button and resin manufacturer.

AFCONA – 7204 has very good compatibility with resin but maintaining as moderate defoamer.

Note: AFCONA – 7204 may become slightly hazy at temperatures below 5° C. This will not influence the quality.

Product specification

Active ingredients	<= 1%
Solvents	DIBK/Alkylbenzene
Density at 20 °C	0.85 - 0.87 g/cm ³
Refractive index	1.479 - 1.489
Flashpoint	42 °C
Appearance	transparent colourless to light yellowish liquid

Addition and dosage

0.2 – 1.0% based on total formulation

Incorporation

AFCONA – 7204 can be used in pre-mix or after mix. Very easy incorporation in clear systems.

Storage

AFCONA-7204 should be stored in a cool dry place. When kept in an original unopened container, it will keep up to 5 years from the date of manufacture. The expiry date is indicated on the container

Packaging

25 kg and 180 kg non-returnable containers